

# WEKSLER®

**100mm Gauge**  
**±1.0 % Accuracy**  
**316 St. St. Tube & Socket**

## STANDARD FEATURES

**Movement:** 300 series stainless steel

**Pointer:** Micrometer adjustable

**Dial:** White enameled aluminum

**Dial Size:** 100mm – dry or glycerin filled

**Connection Location:** 1/4 NPT or 1/2 NPT lower (bottom)

**Case:** Polished 304 stainless steel

Hermetically sealed

Dry version is liquid fillable in field

304 stainless steel case and bezel

**Bourdon Tube & Socket:** 316 stainless steel

- Suitable for a broad range of industrial applications



## PRESSURE RANGES

SPECIFY 10 DIGIT CATALOG NUMBER FROM THE TABLE BELOW

RANGE  DUAL SCALE PSI & KPA	10 DIGIT CATALOG NUMBERS			
	DRY GAUGE		GLYCERIN FILLED GAUGE	
	1/4 NPT	1/2 NPT	1/4 NPT	1/2 NPT
HG vac & 100-0 kPa	N/A	BA4CYVC2LW	BY4CYVC4LW	BY4CYVC2LW
30"-0-30 psi & 100-0-200 kPa	BA4CYCB4LW	BA4CYCB2LW	BY4CYCB4LW	BY4CYCB2LW
30"-0-60 psi & 100-0-400 kPa	BA4CYCC4LW	N/A	BY4CYCC4LW	BY4CYCC2LW
30"-0-150 psi & 100-0-1000 kPa	N/A	N/A	BY4CYCE4LW	BY4CYCE2LW
0-15 psi & 0-100 kPa	BA4CYPC4LW	BA4CYPC2LW	BY4CYPC4LW	BY4CYPC2LW
0-30 psi & 0-200 kPa	BA4CYPD4LW	BA4CYPD2LW	BY4CYPD4LW	BY4CYPD2LW
0-60 psi & 0-400 kPa	BA4CYPE4LW	BA4CYPE2LW	BY4CYPE4LW	BY4CYPE2LW
0-100 psi & 0-700 kPa	BA4CYPF4LW	BA4CYPF2LW	BY4CYPF4LW	BY4CYPF2LW
0-160 psi & 0-1100 kPa	BA4CYPG4LW	BA4CYPG2LW	BY4CYPG4LW	BY4CYPG2LW
0-200 psi & 0-1400 kPa	BA4CYPH4LW	BA4CYPH2LW	BY4CYPH4LW	BY4CYPH2LW
0-300 psi & 0-2100 kPa	BA4CYPJ4LW	BA4CYPJ2LW	BY4CYPJ4LW	BY4CYPJ2LW
0-600 psi & 0-4200 kPa	BA4CYPM4LW	BA4CYPM2LW	BY4CYPM4LW	BY4CYPM2LW
0-1000 psi & 0-7000 kPa	BA4CYPV4LW	BA4CYPV2LW	BY4CYPV4LW	BY4CYPV2LW
0-2000 psi & 0-14000 kPa	N/A	N/A	N/A	BY4CYPV2LW
0-3000 psi & 0-21000 kPa	N/A	BA4CYPT2LW	N/A	BY4CYPT2LW
0-5000 psi & 0-35000 kPa	N/A	N/A	BY4CYPV4LW	BY4CYPV2LW

## HOW TO ORDER

1. Select 10-digit Catalog No. From Table Above