

**Product Specification**

**LEAD FREE\***

**Features ■**

- Eliminates installation of under-the-counter thermostatic valve
- Powers' Advance Thermal Actuator quickly compensates for pressure and temperature fluctuations
- Mixes hot and cold water to deliver tempered water within specified range
- Heavy duty Lead Free\* brass body for durability and to comply with Lead Free\* installation requirements
- Copper supplies feature integrated check valves
- Self-contained cartridge installs in a minute to simplify repairs
- Limits flow to less than 0.5 gpm in the event of cold water failure
- ADA Compliant
- ASSE 1070, IAPMO cUPC listed, and NSF 61 Section 9 Annex G



**Specifications ■**

- Connections ..... 3/8" (10 mm) compression inlets with checks
- Maximum Operating Pressure ..... 125psi (861 kPa)
- Maximum Hot Water Temperature ..... 194°F (90°C)
- Minimum Hot Water Supply Temperature .... 5°F (3°C) Above Set Point
- Temperature Adjustment Range ..... 60 – 120°F (15 – 49°C)
- Minimum Flow to ASSE 1070 ..... 0.5 gpm (1.9 lpm)
- Cold Water Inlet Temperature Range ..... 39 – 80°F (4 – 27°C)
- Hot Water Inlet Temperature Range ..... 120 – 180°F (49 – 82°C)
- Factory Set Temperature ..... 105°F (41°C)
- Listing ..... ASSE 1070, IAPMO cUPC
- Approval Standards ..... ASSE 1070, CSA B125.3, NSF 61 Section 9 Annex G


*\*The wetted surface of this product contacted by consumable water contains less than one quarter of one percent (0.25%) of lead by weight.*

**Capacity Table\*\* ■**

Min. Flow to ASSE 1070	C <sub>v</sub>	10psi (69 kPa)	20psi (138 kPa)	30psi (207 kPa)	45psi (310 kPa)	60psi (414 kPa)
0.5 gpm 1.89 lpm	0.345	1.08 gpm 4.09 lpm	1.53 gpm 5.79 lpm	1.88 gpm 7.12 lpm	2.30 gpm 8.71 lpm	2.60 gpm 9.48 lpm

\*\*Less aerator & outlet temperature 105°F (41°C)

**Dimensions ■**



**Typical Specification ■**

Faucet shall feature solid Lead Free\* brass cast housing and brass limit stop to prevent over adjustment of handle. Faucet shall be listed to ASSE 1070 and IAPMO cUPC for temperature and pressure protection with a minimum control flow of 0.5 gpm (1.9 lpm). Faucet shall feature a single cartridge design for ease of repair and maintenance and shall provide an approach temperature of no greater than 5°F (3°C). Faucet shall include integral check valves to prevent cross flow and have a metal lever handle in compliance with the American with Disabilities Act (ADA). Faucet shall feature ceramic disc mixing and shall be constructed using Lead Free\* material which shall comply with state codes & standards, where applicable requiring reduced lead content.

Faucet shall be Powers model \_\_\_\_\_.

**Ordering Information ■**

Description	Order Code
<input type="checkbox"/> Gooseneck Spout & 2.0 gpm Aerator	205
<input type="checkbox"/> Gooseneck Spout & 2.0 gpm Vandal Resistant Aerator	205VA
<input type="checkbox"/> Gooseneck Spout, 6" Lever Handle & 2.0 Aerator	205-6
<input type="checkbox"/> Gooseneck Spout & 0.5 gpm Outlet	205A5
<input type="checkbox"/> Gooseneck Spout & 0.5 gpm Vandal Resistant Outlet	205V5
<input type="checkbox"/> Gooseneck Spout & 1.5 gpm Aerator+	205A15
<input type="checkbox"/> Gooseneck Spout & 2.0 gpm Laminar flow outlet	205L
<input type="checkbox"/> Gooseneck Spout & 2.0 gpm Vandal Resistant Laminar flow outlet	205VL
<input type="checkbox"/> Gooseneck Spout & 0.5 gpm Laminar flow outlet	205L5
<input type="checkbox"/> Gooseneck Spout & 0.5 gpm Vandal Resistant Laminar flow outlet	205VL5
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 2.0 gpm Aerator	215
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 2.0 gpm Vandal Resistant Aerator	215VA
<input type="checkbox"/> Gooseneck Spout, Deck Plate, 6" Lever Handle & 2.0 Aerator	0215-6
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 0.5 gpm Outlet	215A5
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 0.5 gpm Vandal Resistant Outlet	215V5
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 1.5 gpm Aerator+	215A15
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 2.0 gpm Laminar flow outlet	215L
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 2.0 gpm Vandal Resistant Laminar flow outlet	215VL
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 0.5 gpm Laminar flow outlet	215L5
<input type="checkbox"/> Gooseneck Spout, Deck Plate & 0.5 gpm Vandal Resistant Laminar flow outlet	215VL5

Add following suffix at the end of the order code for:

Grid Drain*	GD
Offset Grid Drain*	OGD

+WaterSense® applies to 1.5 gpm aerator models only.

\*Not listed to IAPMO cUPC

WaterSense® is a registered trademark of the EPA.

ENGINEERING APPROVAL	
Project:	_____
Contractor:	_____
Architect/Engineer:	_____

**POWERS™**

A Watts Water Technologies Company



USA: Phone: 1.800.669.5430 • Fax 1.847.229.0526 • www.powerscontrols.com  
 Canada: Phone: 1.888.208.8927 • Fax 1.888.479.2887 • www.powerscontrols.ca