



**Monitor temperature** with the Series TI Temperature Indicator. Units offer a temperature range of -58 to 99°F (-50 to 99°C) with an accuracy of  $\pm 1\%$ . Quickly view temperatures on the bright red, double-digit LED. Models TI-106 & TI-216 feature an external potentiometer for probe temperature adjustment. The compact design of the Series TI makes it ideal for any refrigeration application.

Model	Power Supply	Display	Adjustable
TI-10	110 VAC	°F	No
TI-21	230 VAC	°C	No
TI-106	110 VAC	°F	Yes
TI-216	230 VAC	°C	Yes

## SPECIFICATIONS

Range: -58 to 99°F (-50 to 99°C). Input: PTC thermistor (1000 $\Omega$  @ 25°C), not included. Power Requirements: 110 VAC or 230 VAC (depending on model). Accuracy: ±1% FS. Display: 2-digit plus sign, red, 1/2″ H digits. Resolution: 1°. Front Panel Rating: NEMA 4X (IP65). Weight: 2.3 oz (65 g). Agency Approvals: CE, UL, ULc.

## ACCESSORIES

**TS-5**, PTC thermistor probe PVC (5 ft cable) **TS-6**, PTC thermistor probe metal (5 ft cable)

Distributed By: M&M Control Service, Inc. www.mmcontrol.com/Love\_Controls.php

800-876-0036 847-356-0566